



FORMATIONS

**FORMICA® ADHESIVES**

FORMATIONS INVENTORY GUIDE

INDUSTRIAL STRENGTH ADHESIVES FOR  
THE WOOD WORKING COMMUNITY



## WOOD GLUES GENERAL ASSEMBLY

### F714 YELLOW GOLDEN GLUE

Medium setting yellow PVA glue for assembly of hard and softwoods. Ideal for edge gluing, doweling and joint assembly.

Sands easily, yellow colour helps conceal glue lines.

- 44% solids
- 5 Minute open time
- 40 minute press time
- Brush grade

ADH- 000141 5 gal format  
ADH- 000140 1 gal format



### F522 WHITE FAST-SET PVA GLUE

Ultra fast-setting white PVA glue for assembly of hard and softwoods. Ideal for edge gluing, dowelling and joint assembly. Sands easily.

- 60% solids
- 10 Minute open time
- 60 minute press time
- Cold press capable
- Brush and roll-able

ADH- 000137 5 gal format  
ADH- 000136 1 gal format



### F715 WHITE PVA GLUE

Medium setting white PVA glue for assembly of hard and softwoods. Ideal for edge gluing, dowelling and joint assembly. Sands easily.

- 45% solids
- 10 Minute open time
- 40 minute press time
- Cold press capable
- Brush and roll-able

ADH- 000157 5 gal format  
ADH- 000156 1 gal format





## WOOD GLUES COLD & HOT PRESS LAMINATING

### F2600 PVA GLUE

Medium setting white PVA glue for Cold and Hot pressing.  
Purpose built for veneer and HPL laminating.  
( works well as a general assembly glue also )



- 45% solids
- 10 Minute open time
- 40 minute press time
- Aggressive 'wet grab'
- Cold and Hot Press capable
- Brush and roll-able

ADH- 000138      5 gal format  
ADH- 000139      55 gal drum format

## CONTACT ADHESIVES WATERBORNE

### F180 WATERBASE CONTACT

High strength waterbased  
neoprene contact cement

- 50% solids
- 60 Minute open time
- Fast tack time
- Excellent adhesion to a variety of substrates
- High heat resistance for high speed postforming applications
- Extremely low VOC content

ADH- 000134      1 gal format  
ADH- 000135      5 gal format



# CANISTER ADHESIVE SYSTEMS

## F200 HIGH PERFORMANCE CONTACT SYSTEMS

High performance contact cement - high temperature capable. Web spray pattern features super fast 'initial grab' with excellent adhesion to a large variety of substrates. Easy, portable system !

- 1 - 3 minute dry time
- 30 minute open time

ADH- 000145 16oz Spray Can Adhesive - Clear  
ADH- 000146 16oz Spray Can Adhesive - Red  
ADH- 000147 38lbs Pressure canister - Clear  
ADH- 000148 38lbs Pressure canister - Red  
ADH- 000149 177lbs Pressure canister - Clear  
ADH- 000150 177lbs Pressure canister - Red

\* 355 lbs canisters are also available - please inquire

Guns, hoses and tips for systems are available from Formations



## F268 NON-FLAMMABLE HIGH PERFORMANCE CONTACT

Non-flammable propellant *and* adhesive. High performance contact cement - high temperature capable. Web spray pattern features super fast 'initial grab' with excellent adhesion to a large variety of substrates. Easy, portable system !

- 1 - 3 minute dry time
- 30 minute open time

ADH- 000153 162lbs Pressure canister - Green

Guns, hoses and tips for systems are available from Formations



# FORMICA® ADHESIVES

INDUSTRIAL STRENGTH ADHESIVES  
FOR THE WOODWORKING COMMUNITY

[formationswood.com](http://formationswood.com)

NORTHERN ALBERTA  
EDMONTON

SOUTHERN ALBERTA  
CALGARY

BRITISH COLUMBIA  
LANGLEY

MANITOBA  
WINNIPEG

SASKATCHEWAN  
REGINA  
SASKATOON